

## Enphase IQ Envoy

The **Enphase IQ Envoy™** communications gateway delivers solar production and energy consumption data to Enphase Enlighten™ monitoring and analysis software for comprehensive, remote maintenance and management of the Enphase IQ System.

With integrated revenue grade production metering and optional consumption monitoring, Envoy IQ is the platform for total energy management and integrates with the Enphase Ensemble™ and the Enphase IQ Battery™.



### Smart

- Enables web-based monitoring and control
- Bidirectional communications for remote upgrades
- Supports power export limiting and zeroexport applications

### Simple

- Easy system configuration using Enphase Installer Toolkit™ mobile app
- Flexible networking with Wi-Fi, Ethernet, or cellular

### Reliable

- Designed for installation indoors or outdoors
- Five-year warranty



To learn more about Enphase offerings, visit [enphase.com](https://enphase.com)

# Enphase IQ Envoy

## MODEL NUMBERS

|                                     |   |
|-------------------------------------|---|
| Enphase IQ Envoy™<br>ENV-IQ-AM1-240 | Enphase IQ Envoy communications gateway with integrated revenue grade PV production metering (ANSI C12.20 +/- 0.5%) and optional consumption monitoring (+/- 2.5%). Includes one 200A continuous rated production CT (current transformer). |
|-------------------------------------|---|

## ACCESORIES (Order Separately)

|  |   |
|--|---|
| Enphase Mobile Connect™<br>CELLMODEM-M1 (4G based LTE-M/5-year data plan)<br>CELLMODEM-M1-B (4G-based LTE-M1/5-year data plan) | Plug and play industrial grade cellular modem with data plan for systems up to 60 microinverters. (Available in the US, Canada, Mexico, Puerto Rico, and the US Virgin Islands, where there is adequate cellular service in the installation area.) |
| Consumption Monitoring CT<br>CT-200-SPLIT  | Split-core consumption CTs enable whole home metering.  |
| Ensemble Communications Kit<br>COMMS-KIT-01  | Installed at the IQ Envoy. For communications with Enphase Encharge™ storage and Enphase Enpower™ smart switch. Includes USB cable for connection to IQ Envoy or Enphase IQ Combiner™ and allows wireless communication with Encharge and Enpower.  |

## POWER REQUIREMENTS

|                           |   |
|---------------------------|---|
| Power requirements        | 120/240 VAC split-phase.<br>Max 20 A overcurrent protection required. |
| Typical Power Consumption | 5W  |

## CAPACITY

|                                 |           |
|---------------------------------|-----------|
| Number of microinverters polled | Up to 600 |
|---------------------------------|-----------|

## MECHANICAL DATA

|                           |  |
|---------------------------|--|
| Dimensions (WxHxD)        | 21.3 x 12.6 x 4.5 cm (8.4" x 5" x 1.8")  |
| Weight                    | 17.6 oz (498 g)  |
| Ambient temperature range | -40° to 65° C (-40° to 149° F)<br>-40° to 46° C (-40° to 115° F) if installed in an enclosure  |
| Environmental rating      | IP30. For installation indoors or in an NRTL-certified, NEMA type 3R enclosure.  |
| Altitude                  | To 2000 meters (6,560 feet)  |
| Production CT             | - Limited to 200A of continuous current / 250A OCPD – 72kW AC<br>- Internal aperture measures 19.36mm to support 250MCM THWN conductors (max)  |
| Consumption CT            | - For electrical services to 250A with parallel runs up to 500A<br>- Internal aperture measures 0.84" x 0.96" (21.33mm x 24.38mm) to support 3/0 THWN conductor<br>- CT wire insulation rating of 600V |

## INTERNET CONNECTION OPTIONS

|                  |  |
|------------------|--|
| Integrated Wi-Fi | 802.11b/g/n  |
| Ethernet         | 802.3, Cat5E (or Cat 6) UTP Ethernet cable (not included)  |
| Mobile           | CELLMODEM-M1 (4G) or CELLMODEM-M1-B (4G). Not included. Note that an Enphase Mobile Connect cellular modem is required for all Ensemble installations. |

## COMPLIANCE

|            |  |
|------------|--|
| Compliance | UL 61010-1<br>CAN/CSA C22.2 No. 61010-1<br>47 CFR, Part 15, Class B, ICES 003<br>IEC/EN 61010-1:2010,<br>EN50065-1, EN61000-4-5, EN61000-6-1, EN61000-6-2<br>Metering: ANSI C12.20 accuracy class 0.5 (PV production only) |
|------------|--|

To learn more about Enphase offerings, visit [enphase.com](https://enphase.com)

© 2021 Enphase Energy. All rights reserved. Enphase, the Enphase logo, IQ Envoy, and other trademarks or service names are the trademarks of Enphase Energy, Inc. Data subject to change.  
2021-03-29

